OFFICE OF THE STATE FIRE MARSHAL


Fire Extinguisher & Automatic Fire Suppression Systems Service Tags & Sticker Samples with Instructions

After the maintenance and service of fire extinguishers or automatic fire suppression systems, a *Service Tag* like the sample below shall be placed as described in R-710.1.6 and R-710.7.5, conspicuously, readily accessible, visible, and in such a position as to be conveniently inspected, on the unit, cylinder or cylinder cabinet. Service tags and service stickers shall be provided by the licensee/contractor and shall meet the minimum qualifications listed below.

- 1. Service tags shall be not more than five and one-half inches (5.5") in height, nor less than four and one-half inches (4.5") in height, and not more than three inches (3") in width, nor less than two and one-half inches (2.5") in width.
- 2. Service Tags may be any color except RED, with contrasting, readable text.

•	BY ORDER OF			(Model No.)
1 2 3 16 17 18	ТҮРЕ	OCT. NOV. DEC.	2017	OWNER'S I.D. NO. (If used) REMARKS Dry and Wet Chemical Fixed
4 5 19 20		AUG. SEPT. OCT.	16	Temperature-Sensing Element Data Year Manufactured
6 7 21 22	E: C.R. No. EE:		201	MONTHLY INSPECTION RECORD DATE BY DATE BY
8 9 10 23 24 25	Your Company	V JUN. JUL.	2015	
11 12 26 27	Name & Address Here	MAR. APR MAY	2014	
13 14 15 28 29 30 31	☐ Recharge d/c □ □ Repair m/p □	EB.	2013	


- 3. The Service Tag must contain all of the items listed in the sample below and be pre-printed, with the following information:
 - Fire Marshal's Seal of Registration. (R-710.1.5)
 - Contrasting background, DO NOT REMOVE BY ORDER OF THE STATE FIRE MARSHAL
 - Company name or identifier (logo) with the company's full address and 24 hour emergency service contact phone number.
 - Concern License registration "E" number or "H" number or both.
 - Technician name. (Signature line)
 - Certificate of Registration "EE" number or "HE" Number or both with (number line).
 - All information pertaining to complete date of service; year, month, day of service.
 - Information regarding type of service performed type on extinguisher and/or type of system.
 - No more than five (5) service years may be placed on a single tag.
 - This information shall be clearly punched, using a hand punch into the tag or sticker.
 - Major deficiencies, shall be written on the tag or a red tag shall be affixed with reference to the deficiency or the extinguisher or cylinder shall be removed from service.
- 4. The tag or sticker shall be writeable and made of a heat resistant, self-destructing material with an affixing fashioner or self-sticking adhesive on the back.



JAN.	FEE	3.	MA	R.	A	PR.		MA	Y	JU	NE	П	S
6	R. MA	INT					HY	DR	0.T	EST			2017 S
		1	loui			bany dres		am	e				2016
				u			99						2015
					ne	ere							
HUN	DREDS	1		3	4	5	6	7	8	9	0	1	14
TESTED	TENS	1	2	3	4	5 5	6	7	8	9	0	E	20
TO (P.S.I.)	UNITS	1	2	3	4	5	6	7	8	9	0	EST	13
JULY	AUG	ì.	SE	PT.	0	CT.	1	NON	Ι.	DE	C.	F	20

- 5. Service stickers are to follow the same design specifications as required for the Service Tags.
- The 6-Year Maintenance and 12 year Hydrostatic Test sticker shall be uniform and follow the NFPA 10.A.8.7.2 design requirement. All print should be black on a silver background.
- 7. Verification-of-Service Collar (Maintenance or Recharging)
 - Each extinguisher thata has undergone maintenance that includes internal examination or that has been recharged shall have a verific ation-of-service collar located around the neck of the container.

b. The collar shall contain a single circular piece of uninterrupted material forming a hole of a size that does not permit removal of the ring when service is complete.



c. The collar shall include the following information. Month and year the service was performed, indicated by a perforation such as is done by a hand punch and name of the agency performing the maintenance or recharge.

The Fire Marshal's Seal of Registration

No person shall produce, reproduce, or use this seal in any manner or for any purpose except as provided by the Administrative Rules R-710.1.6 and R-710.7.5 or with permission from the SFM.



OFFICE OF THE STATE FIRE MARSHAL